

BT11RF



Model:	BT 11 RF
Capacity:	61 cu ft R, 4.5 cu ft F
Temperature Range:	R: 1°C to 7°C (33°F to 45°F), F: -18°C to -23°C (0°F to -10°F)
Exterior Dimensions:	68-1/2"h x 24-1/8"w x 24-1/2"d 173cm x 61cm x 62cm
Interior Dimensions:	R: 28"h x 21"w x 20-3/4"d F: 24-3/4"h x 19"w x 18-1/4"d
Doors:	2 each, one each section with locks
Legs:	Leveling legs
Shelves:	R: (2) adjustable wire F: (1) removable wire
Interior Lighting:	No
Insulation: Walls	R: 1-1/4"; F: 2-1/4" non CFC urethane foam in place
Insulation: Door	R: 1-1/4"; F: 2-1/8" non CFC urethane foam in place
Refrigerant:	R134a

Compressor:	(2 each) R: 1; F: 1 / 457 BTU
Condenser:	(2 each) R: 1; F: 1 / fin and tube fan forced air
Air Circulation:	Natural convection evaporator / fan forced air condensers
Refrigerant Control:	Fixed capillary tube
Evaporator:	Aluminum plate-type
Temperature Control:	Electronic with control knob adjustment; dual digital temperature display
Defrost:	R: auto cycle; F: manual
Voltage:	115 / 60 / 1
Export:	Not available
Running Amps:	6.6
Supply Plug:	Single NEMA-5
Shipping: Cubic Feet	34 cu ft
Weight: lbs. domestic	270 lbs., 123 kg
Export:	Not available

PMC Scientific Division

Ty Altman

2000 SE Hanna Harvester Dr. • Milwaukie, OR 97222-7575
866-656-7400 • Fax: 503-656-6374