

## BT61RFMS



<b>Model:</b>	BT 61 RFMS
<b>Capacity:</b>	6.1 cu ft, 173 litres
<b>Temperature Range:</b>	1°C to 7°C (33°F to 45°F)
<b>Exterior Dimensions:</b>	34"h x 23-7/8"w x 26"d 86cm x 61cm x 66cm
<b>Interior Dimensions:</b>	28"h x 21"w x 20-3/4"d 71cm x 53cm x 53cm
<b>Doors:</b>	Left with lock
<b>Legs:</b>	Leveling
<b>Shelves:</b>	2, adjustable
<b>Interior Lighting:</b>	None
<b>Insulation: Walls</b>	1-1/4" non CFC urethane foam in place
<b>Insulation: Door</b>	1-1/4" non CFC urethane foam in place
<b>Refrigerant:</b>	R134a
<b>Compressor:</b>	Bottom-mounted / 330 BTU

<b>Condenser:</b>	Static fin and tube, rear of cabinet mounted
<b>Air Circulation:</b>	Natural convection for both evaporator and condenser
<b>Refrigerant Control:</b>	Fixed capillary tube
<b>Evaporator:</b>	Aluminum plate-type
<b>Temperature Control:</b>	Mechanical vapor pressure (totally enclosed), adjustable
<b>Defrost:</b>	Autocycle
<b>Voltage:</b>	115 / 60 / 1
<b>Export:</b>	Not available
<b>Running Amps:</b>	2.5
<b>Supply Plug:</b>	NEMA-5
<b>Shipping: Cubic Feet</b>	16.8 cu ft
<b>Weight: lbs. domestic</b>	120 lbs., 55 kg
<b>Export:</b>	Not available

## PMC Scientific Division

*Ty Altman*

2000 SE Hanna Harvester Dr. • Milwaukie, OR 97222-7575  
866-656-7400 • Fax: 503-656-6374